

NSPEC CAT 5E CMP (350MHz) PLENUM

Description NSPEC Cat 5e Plenum offers unbeatable value, as this fully ANSI/TIA.EIA-568-B.2-compliant cable comes at a very practical price. NSPEC Cat 5e is meter-marked for easy measuring and comes in a durable box with special features for fast and effortless installation

Conductor Solid bare copper
Insulation Fluorinated Ethylene Polymer (FEP)
Jacket Flame Retardant, Low Smoke PVC
Insulation Colours Pair 1: White-Blue / Blue
 Pair 2: White-Orange / Orange
 Pair 3: White-Green / Green
 Pair 4: White-Brown / Brown

Compliance UL Verified to Category 5e
 UL 444 UL Listed CMR (UL 1666)
 UL Listed CMP (NFPA 262)
 ISO/IEC 11801
 ANSI/TIA/EIA 568-B.2
 ANSI/ICEA S-90-661-2002
 RoHS Compliant

Applications 10BASE-T through 1000BASE-T Ethernet
 Power over Ethernet (PoE) – IEEE 802.3af
 PoE+ - IEEE 802.3at Type 1 and 2
 ATM and token ring



Product Code	AWG	Pair Count	Nom Diameter in (mm)	Nom Impedance (ohms)	Nom Velocity of Prop. (%)	Approx Weight lbs/kft (kg/km)	Jacket Colour
425EU10	24	4	0.19(4.8)	100± 15	73	20(30)	White
425EU10	24	4	0.19(4.8)	100± 15	73	20(30)	Blue
425EU10	24	4	0.19(4.8)	100± 15	73	20(30)	Yellow